

## WHAT IS CLAIMED IS:

1. (original) A vehicle light for motor vehicles, the vehicle light comprising:  
at least one vehicle light housing configured to be arranged on an inner side of a vehicle part of the vehicle, wherein the vehicle part has at least one mounting opening for mounting the at least one vehicle light housing;  
at least one illumination element arranged in the at least one vehicle light housing;  
wherein the vehicle light housing comprises a lens of light-transmissive material mounted in the at least one mounting opening such that an exterior side of the light-transmissive lens is flush with an outer side of the vehicle part;  
a light-transmissive coating applied onto the exterior side of the lens, wherein the light-transmissive coating has a color matching a color of a coating of the vehicle part and wherein the light-transmissive coating has a thickness such that the lens when the at least one illumination element is switched off is invisible from the exterior of the vehicle and such that the lens allows light emitted by the at least one illumination element to pass through when the at least one illumination element is switched on.
2. (original) The vehicle light according to claim 1, wherein the vehicle part is a trunk lid of the vehicle.
3. (original) The vehicle light according to claim 1, wherein the vehicle part is a rear hatch of the vehicle.
4. (original) The vehicle light according to claim 1, wherein the vehicle part is comprised of light-opaque material.
5. (original) The vehicle light according to claim 4, wherein the vehicle part is made of metal.
6. (original) The vehicle light according to claim 1, wherein the vehicle part is comprised of plastic material.
7. (original) The vehicle light according to claim 6, wherein the plastic material is a light-transmissive material.
8. (original) The vehicle light according to claim 7, wherein the plastic material is coated with a coat of paint.
9. (original) The vehicle light according to claim 1, wherein the vehicle part and the lens are comprised of light-transmissive plastic material.

10. (original) The vehicle light according to claim 9, wherein the light-transmissive plastic material of the vehicle part and the light-transmissive plastic material of the light-transmissive area are identical.

11. (original) The vehicle light according to claim 1, wherein the lens has an edge, wherein between the edge of the lens and an edge of the mounting opening a gap is defined, and wherein the gap is covered.

12. (original) The vehicle light according to claim 11, wherein the gap is covered from the outer side of the vehicle part.

13. (original) The vehicle light according to claim 12, comprising a cover element connected to the outer side of the vehicle part, wherein the gap is covered by the cover element.

14. (original) The vehicle light according to claim 13, wherein the cover element is an emblem or a symbol.

15. (original) The vehicle light according to claim 13, wherein the cover element is light-opaque.

16. (original) The vehicle light according to claim 14, wherein the vehicle part is at least partially light-transmissive in an area underneath the emblem.

17. (original) The vehicle light according to claim 14, wherein the vehicle part is light-opaque in an area surrounded by the emblem.

18. (original) The vehicle light according to claim 11, wherein the gap is covered from the inner side of the vehicle part.

19. (original) The vehicle light according to claim 18, further comprising at least one sealing element, wherein the lens comprises at least one support part arranged at a spacing from the inner side of the vehicle part and configured to receive the at least one sealing element.

20. (original) The vehicle light according to claim 19, wherein the at least one sealing element is an O-ring.

21. (original) The vehicle light according to claim 19, wherein the at least one support part is an annular flange projecting radially from the lens.

22. (original) The vehicle light according to claim 19, wherein the at least one vehicle light housing has a shoulder surface and wherein the at least one support part rests

against the shoulder surface.

23. (original) The vehicle light according to claim 1, wherein the lens is centered by the at least one vehicle light housing.

24. (original) The vehicle light according to claim 1, further comprising at least one optical element positioned in a path of light rays emitted by the at least one illumination element.

25. (original) The vehicle light according to claim 24, wherein the at least one optical element is a Fresnel lens.

26. (previously presented) A vehicle light for motor vehicles, the vehicle light comprising:

at least one vehicle light housing comprising a lens and configured to be arranged on an inner side of a continuous vehicle part of the vehicle, wherein the vehicle part consists of a light-transmissive material;

at least one illumination element arranged in the at least one vehicle light housing and emitting light through the lens;

a light-transmissive coating applied onto an outer side of the vehicle part, wherein the light-transmissive coating has a thickness in an area of the lens such that, when the at least one illumination element is switched off, the lens is invisible from the exterior of the vehicle and such that light emitted by the at least one illumination element passes through the coating when the at least one illumination element is switched on.

27. (currently amended) A vehicle light for motor vehicles, the vehicle light comprising:

at least one vehicle light housing configured to be arranged on an inner side of a continuous ~~carbody~~ car body part, wherein the ~~carbody~~ car body part has perforation openings filled in with light-transmissive material in an area behind which the at least one vehicle light housing is arranged;

at least one illumination element arranged in the at least one vehicle light housing;

wherein light emitted by the at least one illumination element passes through the perforation openings when the at least one illumination element is switched on.

28. (previously presented) The vehicle light according to claim 27, wherein the perforation openings are coated with a coating so thick that the perforation openings

cannot be detected from the exterior but allow passage of light.

29. (currently amended) The vehicle light according to claim 28, wherein the coating has a color that is identical to a color of a coating of the ~~carbody~~ car body part.

30.-35. (canceled)